

Shrink Tubing – Dual Wall

- 3:1 Ratio
- Adhesive lined Polyolefin
- Meets UL and MIL=DTL-23053/4 class 3



Cat. No	Wire GA.	Color	Exp. I.D.	After Recovery	Pieces or Ft.
20730	6-4	Black	.375"	.120"	6-6"
20730-48	6-4	Black	.375"	.120"	1-48"
20731	2-1	Black	.500"	.160"	6-6"
20731-48	2-1	Black	.500"	.160"	1-48"
20732	1/0-4/0	Black	1.000"	.320"	6-6"
20734	1/0-4/0	Black	1.000"	.320"	1-48"
20733	1/0-4/0	Red	1.000"	.320"	6-6"
20735	1/0-4/0	Red	1.000"	.320"	1-48"

Polyethylene Split Loom - Black

- Temperature Range -40°F to 200°F
- Good Abrasion Resistance
- Excellent Resistance to Auto Fluids and Chemicals
- Split seam allows easy wire service and insertion



Size	25' Bag #	100' Box #	250' Box #	Big Box #
1/4"	50014T	50014C	50014L	50014-3200'
3/8"	50038T	50038C	50038L	50038-1900'
1/2"	50012T	50012C	50012L	50012-1100'
5/8"	50058T	50058C	50058L	50058-800'
3/4"	50034T	50034C	50034L	50034-600'
1"	50001T	50001C	50001L	50001-350'
1 1/4"	50114T	50114C	50114L	
1 1/2"	-	-	-	50112-150'
2"	-	50002C	-	-

Nylon Cable Ties

- Standard Pack of 100
- Made in USA



Length	Tensile Strength	Bundle Diameter	Natural #	UV Black #
4"	18 lbs.	.625"	18-04	18-04BL
5.5"	30 lbs.	1.25"	18-05	18-05BL
6.4"	18 lbs.	1.5"	18-06	18-06BL
7.5"	50 lbs.	1.75"	18-07	18-07BL
8.5"	40 lbs.	2"	18-08	18-08BL
11.5"	50 lbs.	3"	18-11	18-11BL
14.7"	120 lbs.	4"	18-13	18-13BL
14.5"	50 lbs.	4"	18-14	18-14BL
8.2"	50 lbs.	1.75"	18-17	18-17BL